

Product Name: Weller Butane Gas Refill Page: 1 of 6

This revision issued: June, 2022

# Section 1 - Identification of The Material and Supplier

Pascoe's Pty Ltd 40-46 Fairfield St Fairfield East, NSW 2165 Phone: +61 1800 065 326 www.pascoes.com.au

Distributed in New Zealand by
Apex Tool Group NZ
21 Raphael Place, West Harbour
Auckland 0618, New Zealand

Phone: +64 9 608 0227 NZ Poisons Information Centre: +64 800 764 766

Chemical nature: Propane/butane blend.

Trade Name: Weller Butane Gas Refill

Product Use: Dispenser for refilling a range of Cooper Brand Tools.

This version issued: June, 2022 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

## Section 2 - Hazards Identification

# Statement of Hazardous Nature SUSMP Classification: None allocated.

ADG Classification: Class 2.1: Flammable gases.

**UN Number: 1950, AEROSOLS** 



# GHS Signal word: DANGER

Aerosols – category 1

#### **HAZARD STATEMENT:**

H222: Extremely flammable aerosol.

H229: Pressurised container: may burst if heated.

#### **PREVENTION**

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P233: Keep container tightly closed.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P281: Use personal protective equipment as required.

#### **RESPONSE**

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P372: Explosion risk in case of fire.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires.

#### **STORAGE**

P402: Store in a dry place.

P403: Store in a well-ventilated place.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

# **DISPOSAL**

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

#### Statement of Hazardous Nature (New Zealand)

Aerosols Flammable Group Standard 2020 HSR002515

**DG Classification:** Classified as a Dangerous Good for transport in accordance with the Land Transport Rule Dangerous Goods 2005 and NZS 5433:2007.

#### SAFETY DATA SHEET



**Product Name: Weller Butane Gas Refill** Page: 2 of 6

This revision issued: June, 2022

## **Emergency Overview**

Physical Description & Colour: Dispenses as a gas.

Odour: Characteristic odour.

Major Health Hazards: no significant risk factors have been found for this product.

## Section 3 - Composition/Information on Ingredients

TWA (mg/m<sup>3</sup>) Ingredients CAS No Conc,% STEL (mg/m<sup>3</sup>)

Alkanes, C<sub>3-4</sub>

pure \*

not set

not set

68475-59-2

\* Commercially pure. May include small quantities of materials due to manufacturing or reaction processes.

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## Section 4 - First Aid Measures

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

**Skin Contact:** First aid is not generally required.

Eye Contact: No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

**Ingestion:** Not a normal route of exposure If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

## **Section 5 - Fire Fighting Measures**

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

# **Section 6 - Accidental Release Measures**

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

#### **Section 7 - Handling and Storage**

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to

SAFETY DATA SHEET



Product Name: Weller Butane Gas Refill Page: 3 of 6

This revision issued: June, 2022

persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

# **Section 8 - Exposure Controls and Personal Protection**

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits TWA (mg/m³) STEL (mg/m³)

Exposure limits have not been established by SWA for this product.

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** The information at hand indicates that this product is not harmful and that normally no special skin protection is necessary. However, we suggest that you routinely avoid contact with all chemical products and that you wear suitable gloves (preferably elbow-length) when skin contact is likely.

**Protective Material Types:** There is no specific recommendation for any particular protective material type. **Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

#### **Section 9 - Physical and Chemical Properties:**

Physical Description & colour: Dispenses as a gas.

Odour: Characteristic odour.

Boiling Point: Not available.

Flash point: -62°C
Upper Flammability Limit: 9.6%
Lower Flammability Limit: 1.9%
Autoignition temperature: No data.

**Freezing/Melting Point:** No specific data. Gas at normal temperatures and pressures.

**Volatiles:** Completely volatile at 100°C.

**Vapour Pressure:** 350-450kPa at 25°C

**Vapour Density:** >1 Specific Gravity: 0.55 Water Solubility: Insoluble. pH: No data. Volatility: No data. Odour Threshold: No data. **Evaporation Rate:** >1 Coeff Oil/water Distribution: No data

Particle Characteristics: Not applicable to gases.

# Section 10 – Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Containers should be kept dry. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

**SAFETY DATA SHEET** 



Product Name: Weller Butane Gas Refill Page: 4 of 6

This revision issued: June, 2022

**Incompatibilities:** strong oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

# **Section 11 - Toxicological Information**

**Local Effects:** 

**Target Organs:** There is no data to hand indicating any particular target organs.

# **Classification of Hazardous Ingredients**

#### Ingredient

#### Health Hazard Statement Codes

Alkanes, C<sub>3-4</sub>

H220, H330, H350, H340, H319, H315, H335, H372, H360Df

- Gases under pressure
- Flammable gas category 1
- Acute toxicity category 2
- Carcinogenicity category 1A
- Germ cell mutagenicity category 1B
- Eye irritation category 2A
- Skin irritation category 2
- Specific target organ toxicity (single exposure) category 3
- Specific target organ toxicity (repeated exposure) category 1
- Reproductive toxicity category 1B

**NOTE:** Some of the above classifications relate to impurities found in some grades of this ingredient and do not apply to products which do not contain hazardous concentrations of impurities.

#### **Potential Health Effects**

#### Inhalation:

**Short Term Exposure:** Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

**Short Term Exposure:** Major health effect from this product is misuse of the aerosol function. If sprayed

continuously on skin or in eyes, it can cause frostbite.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

**Short Term Exposure:** If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. This product is unlikely to cause any irritation problems in the short or long term.

Long Term Exposure: No data for health effects associated with long term ingestion.

## Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP. **IARC:** No significant ingredient is classified as carcinogenic by IARC.

#### **Section 12 - Ecological Information**

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems. Expected to not be an environmental hazard.

#### SAFETY DATA SHEET



Product Name: Weller Butane Gas Refill Page: 5 of 6

This revision issued: June, 2022

# Section 13 - Disposal Considerations

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

## **Section 14 - Transport Information**

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

ADG Code: 1950, AEROSOLS

Hazchem Code: 2YE

Special Provisions: 63, 190, 277, 327, 344, 381

Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

Dangerous Goods Class: Class 2.1: Flammable gases.

Packing Group: Not set

Packing Instruction: P207, LP200

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

#### **New Zealand**

Classified as Dangerous Goods for transport in accordance with the Land Transport Rule Dangerous Goods 2005 and NZS 5433:2007.

## **Section 15 - Regulatory Information**

**AIIC:** This product is compliant with AICIS regulations.

New Zealand:

Aerosols Flammable Group Standard 2020 HSR002515

#### **Section 16 - Other Information**

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> edition)

AllC Australian Inventory of Industrial Chemicals

SWA Safe Work Australia, formerly ASCC and NOHSC

CAS number Chemical Abstracts Service Registry Number

**Hazchem Code** Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

**UN Number** United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD STATEMENT: INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

#### Australia:

SAFETY DATA SHEET



Product Name: Weller Butane Gas Refill Page: 6 of 6

This revision issued: June, 2022

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020) and GHS Revision 7

## **New Zealand**

HSNO Approved Code of Practice: Preparation of Safety Data Sheets. New Zealand Chemical Industry Council September 2006.

Copyright © Kilford & Kilford Pty Ltd, June, 2022. <a href="http://www.kilford.com.au/">http://www.kilford.com.au/</a> Phone (02)8321 8866

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)